

# uPVC Power Ducting

## Description

uPVC Power duct is a solid wall pipe manufactured under the ISO9001:2008 quality system and in accordance with ENA TS 12-24 and BS EN 61386-24 : 2010. Each length is socketed as standard. Ring seal sockets are available for a range of sizes. A full range of fittings is also available including bends, couplers and hockey sticks.

## Dimensions

Nominal Pipe OD (mm)	Nominal ID (mm)	Wall Thickness (mm)	Length* (m)	Pack Qty (lengths)
<b>Class 1 ENA TS 12-24</b>				
54	49	2.5	6	390
110	102	4.0	6	114
125	116	4.35	6	68
160	150	5.13	6	46
200	188	6.05	6	23
<b>Class 2 ENA TS 12-24</b>				
54	50	2.1	6	390
110	103	3.37	6	114
125	118	3.7	6	68
160	151	4.35	6	46
200	190	5.05	6	23



## Technical

Material	Unplasticised Polyvinyl Chloride (uPVC)
Colour	Black or Red
Print	Every meter with meter count and batch number for traceability. Can be customer specific if required.
Standards	Ducts are manufactured in accordance with ENA TS 12-24 and BS EN 61386-24 : 2010. Manufactured under ISO9001:2008 et ISO14001:2004 systems

Order now from **Tufflite Supplies 01282 433317**  
or email: **sales@tufflite.co.uk**